



4-Stripe Control Panel

Technical Specifications

Stripes	4 x panel stripes independently configurable for switcher, M/E, PREVIZ, or NDI™ output router operation <ul style="list-style-type: none"> • Dynamic LCD crosspoint label displays • Support for bank, layer and key delegation • Support for multi-engine control
Crosspoints	72 x crosspoints per stripe (24 buttons with 3 delegate banks)
COMPs	Direct panel access to VMC1 Video Mix Engine COMP Bin presets
Macro	Macro mode and number pads supporting attachment and activation of user-configured macros
Media	2 x media player control keypad with player delegation and command buttons
MEM	Direct panel access to VMC1 Video Mix Engine switcher and M/E MEMs
T-Bars	4 x multi-mode T-Bars (1 per stripe) with dynamically variable illumination and support for BKGD video layer and key layer delegation <ul style="list-style-type: none"> • Fade • Transition • Fade to Black • LiveSet™ Zoom
Joysticks	2 x multi-mode joysticks (3-axis) supporting stripe, layer and key delegation <ul style="list-style-type: none"> • Position/Scale • Rotate • Crop • LiveSet virtual camera control • PTZ camera control • Media player shuttle
NIC	1 Gigabit NIC
Physical	VMC1 4S chassis with 25W PSU <ul style="list-style-type: none"> • 42.2 x 21.26 x 6.13 in (107.2 x 54.0 x 15.6 cm) • 49.75 lbs (22.57 kg)

Subject to change without notice.
For complete technical specifications, please visit the IP Series page at www.newtek.com.
Multi-standard pricing and availability may vary. Please contact your local reseller for details.